ANIMAL CREMATION



Model A-250P-5 "Hot Hearth" Cremation Equipment

The American A-250P-5 is Ideal for High-Volume facilities that desire completely private cremations while processing multiple pets at the same time. Our Multi-Chamber units are truly independently operated chambers. The A-250P-5 has one ^{8'6}" (2.6m) large chamber in the front and two medium chambers on each side. Each chamber has independent combustion control allowing for the operation of a single chamber or any combination of all five chambers. The A-250P-5 will allow your business to achieve a level of service to your clients that is unparalleled. All of the American models come standard with independent hydraulic loading doors, no counterweight or "cooler" style loading doors. Multi-Chamber units can be wrapped for a very appealing visual experience for your clients while witnessing of private cremations.

> 8'6" (2.6m)

7'8"(2.34m) 8'8"(2.64m) with panel

A-250P-5 Specifications

A-2301 -3 3	becilications						
Length	17'0" (5.18m)						
Width	7'8" (2.34m); 8'8" with panel (2.64m)						
Height	8'6" (2.59m)						
Door Width	40" (1.02m)	40" (1.02m)				•	
Loading Oper	ning 4@29"x36";1@	2 40" x 48"				1 Marco	
Weight	38,000 Lbs. (17,23						
Installation Cle	earance Required	9' min (2.7m); 10' (3.05m) Recommer	bet			Men	
Fuel		Natural Gas, Propane, Butane, Can be Modified to Accept Diesel Oil					
Electrical	220V/60Hz/1 Pho (Nationally)	220V/60Hz/1 Phase or 3 Phase (Nationally)				a	
	240V/50Hz/1 Pho (Internationally)	240V/50Hz/1 Phase or 3 Phase (Internationally)				e e e	
	60 AMP Minimun	n Requirement	8'6" (2.6m)			40° (1.02m	
Maximum Fue	Rating 4.0MMBTU	'HR @ 3809 CFH				200000000	
Panel	Right, Left or Rer	Right, Left or Remote		inersi 6			
Warranty	2 year "Best in C	2 year "Best in Class"			and a second		

17'0 (5.18m)

Available in a wide range of colors allowing you or our team to design a comforting setting for your customers.

Lease & Finance Options Available